

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM OPTIONS

- Sliding mid-rail standard platform
- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform

POWER OPTIONS

- AC power 85V / 50-60 Hz
- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC 12V with 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system
- Air motor power 1.5 hp (1.1 kW) (AWP-30 only)

BASE OPTIONS

- Standard base
- Rough terrain (RT) base (AWP-20, -25, -30 only)



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Super-straddle
- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform
- Narrow base conversion kit (AWP-20, -25, -30 RT only)
- Operational warning light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

POWER

- Air motor power 1.5 hp (1.1 kW) (AWP-30 only)

STANDARD FEATURES

MEASUREMENTS

AWP™-20S

- 26 ft 1 in (8.12 m) working height
- 20 ft 1 in (6.12 m) platform height
- 2 ft 5 in (.74 m) standard base width
- 2 ft 6 in (.76 m) RT base width
- Up to 350 lb (159 kg) lift capacity

AWP™-25S

- 30 ft 10 in (9.57 m) working height
- 24 ft 10 in (7.57 m) platform height
- 2 ft 5 in (.74 m) standard base width
- 2 ft 6 in (.76 m) RT base width
- Up to 350 lb (159 kg) lift capacity

AWP™-30S

- 35 ft 6 in (11.02 m) working height
- 29 ft 6 in (9.02 m) platform height
- 2 ft 5 in (.74 m) standard base width
- 2 ft 6 in (.76 m) RT base width
- Up to 350 lb (159 kg) lift capacity

AWP™-36S

- 42 ft 5 in (13.10 m) working height
- 36 ft 5 in (11.10 m) platform height
- 2 ft 5 in (.74 m) standard base width
- Up to 350 lb (159 kg) lift capacity

AWP™-40S

- 46 ft 4 in (14.29 m) working height
- 40 ft 4 in (12.29 m) platform height
- 2 ft 5 in (.74 m) standard base width
- Up to 300 lb (136 kg) lift capacity

PRODUCTIVITY

- Auxiliary platform lowering
- Most rigid mast in the industry
- Rocker base system for maneuverability
- Tilt back frame (standard on AWP-36, -40)
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt (ANSI / CSA only)
- Small outrigger footprints
- Outrigger storage sockets
- Easy loading in pickup trucks
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Rear access forklift pocket
- LED lights confirm proper set-up




POWER

- AC power 85V / 50-60 Hz
- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system

Specifications

MODELS	AWP™-36S		AWP™-40S	
MEASUREMENTS	US	Metric	US	Metric
Working height*	42 ft 5 in	13.10 m	46 ft 4 in	14.29 m
Platform height	36 ft 5 in	11.10 m	40 ft 4 in	12.29 m
A Height - stowed (Standard)	9 ft 1.5 in	2.78 m	9 ft 1.5 in	2.78 m
stowed (RT)	—	—	—	—
B tilted back** (Standard)	6 ft 3.5 in	1.92 m	6 ft 6 in	1.98 m
C Length - stowed (Standard)	4 ft 7 in	1.40 m	4 ft 8 in	1.42 m
stowed (RT)	—	—	—	—
D Length - tilted back**	9 ft 9 in	2.97 m	9 ft 9 in	2.97 m
E Width (Standard)	2 ft 5 in	.74 m	2 ft 5 in	.74 m
Width (RT)	—	—	—	—

PRODUCTIVITY																																						
Lift capacity	350 lbs	159 kg	300 lbs	136 kg																																		
ANSI/CSA:																																						
F Outrigger footprint (l/w) (Standard)	6 ft 11 in/6 ft 3 in	2.1/1.9 m	7 ft 5 in/6 ft 9 in	2.26/2.06 m																																		
G Outrigger footprint (l/w) (RT)	—	—	—	—																																		
Corner access*** (Standard)	2 ft 5 in	.74 m	2 ft 7 in	.79 m																																		
H Corner access*** (RT)	—	—	—	—																																		
Wall access front/side (Standard)	1 ft 2 in/2 ft 1 in	.36/.64 m	1 ft 3 in/2 ft 4 in	.38/.71 m																																		
I Wall access front/side (RT)	—	—	—	—																																		
CE/AUS/PB Indoor:																																						
Outrigger footprint (l/w) (Standard)	6 ft 11 in/6 ft 3 in	2.12/1.91 m	7 ft 5 in /6 ft 9 in	2.26/2.06 m																																		
F Outrigger footprint (l/w) (RT)	—	—	—	—																																		
Corner access*** (Standard)	2 ft 5 in	.74 m	2 ft 7 in	.79 m																																		
H Corner access*** (RT)	—	—	—	—																																		
Wall access front/side (Standard)	1 ft 2 in/2 ft 1 in	.36/.64 m	1 ft 3 in/2 ft 4 in	.38/.71 m																																		
I Wall access front/side (RT)	—	—	—	—																																		
CE/AUS/PB Outdoor:																																						
Outrigger footprint (l/w) (Standard)	11 ft 7 in/10 ft 11 in	3.53/3.33 m	12 ft 9 in/12 ft 1 in	3.89/3.68 m																																		
F Outrigger footprint (l/w) (RT)	—	—	—	—																																		
Corner access*** (Standard)	3 ft 4 in	1.02 m	3 ft 8 in	1.12 m																																		
H Corner access*** (RT)	—	—	— </tr <tr> <td>Wall access front/side (Standard)</td> <td>3 ft 4 in/4 ft 4 in</td> <td>1.02/1.32 m</td> <td>3 ft 8 in/5 ft</td> <td>1.12/1.52 m</td> </tr> <tr> <td>I Wall access front/side (RT)</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td colspan="5">Platform Dimensions: (l/w/h)</td> </tr> <tr> <td>Standard</td> <td>27/26/44.75 in</td> <td>.69/.66/1.14 m</td> <td>27/26/44.75 in</td> <td>.69/.66/1.14 m</td> </tr> <tr> <td>Gated standard</td> <td>27/26/44.75 in</td> <td>.69/.66/1.14 m</td> <td>27/26/44.75 in</td> <td>.69/.66/1.14 m</td> </tr> <tr> <td>Gated narrow</td> <td>26/20/44.75 in</td> <td>.66/.51/1.14 m</td> <td>26/20/44.75 in</td> <td>.66/.51/1.14 m</td> </tr> <tr> <td>Standard fiberglass</td> <td>29/26.5/43.5 in</td> <td>.74/.67/1.10 m</td> <td>29/26.5/43.5 in</td> <td>.74/.67/1.10 m</td> </tr>	Wall access front/side (Standard)	3 ft 4 in/4 ft 4 in	1.02/1.32 m	3 ft 8 in/5 ft	1.12/1.52 m	I Wall access front/side (RT)	—	—	—	—	Platform Dimensions: (l/w/h)					Standard	27/26/44.75 in	.69/.66/1.14 m	27/26/44.75 in	.69/.66/1.14 m	Gated standard	27/26/44.75 in	.69/.66/1.14 m	27/26/44.75 in	.69/.66/1.14 m	Gated narrow	26/20/44.75 in	.66/.51/1.14 m	26/20/44.75 in	.66/.51/1.14 m	Standard fiberglass	29/26.5/43.5 in	.74/.67/1.10 m	29/26.5/43.5 in	.74/.67/1.10 m
Wall access front/side (Standard)	3 ft 4 in/4 ft 4 in	1.02/1.32 m	3 ft 8 in/5 ft	1.12/1.52 m																																		
I Wall access front/side (RT)	—	—	—	—																																		
Platform Dimensions: (l/w/h)																																						
Standard	27/26/44.75 in	.69/.66/1.14 m	27/26/44.75 in	.69/.66/1.14 m																																		
Gated standard	27/26/44.75 in	.69/.66/1.14 m	27/26/44.75 in	.69/.66/1.14 m																																		
Gated narrow	26/20/44.75 in	.66/.51/1.14 m	26/20/44.75 in	.66/.51/1.14 m																																		
Standard fiberglass	29/26.5/43.5 in	.74/.67/1.10 m	29/26.5/43.5 in	.74/.67/1.10 m																																		



POWER		
Power source - AC or DC models	12V DC / 110/50-60 Hz or 220/50-60 Hz AC	12V DC / 110/50-60 Hz or 220/50-60 Hz AC

WEIGHT				
AC models (Standard)	1,017 lbs	461 kg	1,040 lbs	472 kg
AC models (RT)	—	—	—	—
DC models (Standard)	1,107 lbs	502 kg	1,130 lbs	513 kg
DC models (RT)	—	—	—	—
Air motor (Standard)	—	—	—	—
Air motor (RT)	—	—	—	—

STANDARDS COMPLIANCE	ANSI A92.3, CSA B354.1, EN 280, AS 1418.10
----------------------	--

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Tilt back height with standard platform. For tilt back height with other platforms, please contact your sales representative.
 *** Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.